


It's the "Swiss Army Knife" of Ceiling Support Boxes!




You asked for more versatility, and we delivered.

Why stock two or more ceiling supports when a single box can be used for all three vertical chimney applications?


That's what you get with the **Reduced Clearance Ceiling Support** for use with Security Chimney's Secure Temp® ASHT insulated chimney.



FLAT CEILING



VAULTED CEILING



CATHEDRAL CEILING



RCS shown with standard Square-to-Round Collar

This new box design fulfills plenty of other common requests too. The list of standard features below will quickly make this your go-to ceiling support:

1. Works within Smaller Openings – The RCS is factory-tested and certified to reduce surrounding clearances-to-combustibles around the box from 2" to just 1". This allows a 6" ASHT chimney to be installed within a 10 & 1/8" x 10 & 1/8" opening. Versions of the RCS are also available for use with 7" and 8" pipe too, although framing dimensions will correspond to diameter.

2. Can act as an Attic Radiation Shield* - When the ceiling penetration is right at the attic, fix the square-to-round collar (included at no extra charge) around the chimney, then push down atop the box to complete the assembly. This eliminates the need for a separate Attic Radiation Shield component. Aside from one less part to worry about, assembly is quicker.

3. Integrated Starter Collar and Built-In Stovepipe Adapter – Like other ASHT ceiling supports, the first chimney length simply twist-locks within the support, and the adapter works with both single-wall and double-wall stovepipe. No additional parts are required.

4. Comes with Finish Trim – Our two-piece adjustable trim is pre-painted to match the box. The overlapping ends allow it to work with both flat and pitched ceilings. The end-result is a clean, professional finish.

5. Best of all, the RCS is insulated! – We include a batt of rockwool insulation with each & every RCS box we sell. For both new constructions and retrofit installations. Providing the vapor barrier is secured to the box's perimeter, this factory-sealed assembly will help to minimize leakage of air from conditioned spaces (warm) up into unconditioned spaces (cold). Ideal for today's high-efficient homes.

*RCS Reduced Clearance Ceiling Support has a standard 24" Box Height. A minimum of 3 1/2" must protrude below the ceiling to ensure appropriate clearances for stovepipe. If additional box height is required, a matching 24" Support Box Extension (SE) is available. With 2" overlap, provides up to 22" in additional height. Be sure to read instructions closely prior to starting an installation.

Go to www.securitychimneys.com to view the full product catalog, install instructions and other documents for Secure Temp S2100.

Leaders in-Venting Innovation™

www.securitychimneys.com | 800-361-4909 (US) | 800-667-3387 (Canada)

Sales Sheet ASHT_RCS_07-18-18