



*Fluoroelastomer Adhesives,
Coatings, Sealants, and Caulk*

TECHNICAL DATA

Pelseal® 2531 Application Data Sheet

Color:	Black
Application Method:	Unscrew red cartridge seal and put aside. Do not throw away seal. Screw in plastic nozzle and snip off end of nozzle to desired opening. Load cartridge into appropriate size caulking gun and apply. Reseal cartridge to preserve unused portion.
Substrate Preparation:	A clean, dry surface is essential for maximum adhesion. Gritblasting and degreasing with oil-free solvents is recommended.
Drying:	Although tack free in approximately five minutes at 75° F (24° C), allow a minimum of 72 hours for the solvent to evaporate. Dried compound will be chemically resistant.
Heat Curing:	Tougher materials can be achieved by heating dried material. If solvent is present during heating, blistering may result. Contact Pelseal for guidance to achieve the best results for your specific application.
Successive Coats:	Allow for solvent evaporation prior to making multiple coats, or blisters may result. Product adheres well to itself.
Shelf Life:	12 months from the Date of Certification for unopened containers stored at 75° F (24° C) or below.
Clean Up:	MEK, MIBK and Acetone can be used.
Safety:	FLAMMABLE LIQUID Use in accordance with the Safety Data Sheet.

Pelseal® is a registered trademark of Pelseal® Technologies, LLC

Disclaimer Information and suggestions supplied by Pelseal® Technologies, LLC (“Pelseal”), whether in published literature or otherwise, including samples, are based on technical data that Pelseal believes to be reliable. Such information and suggestions are supplied without charge and their use, and the use of Pelseal’s products, are beyond Pelseal’s control. Pelseal’s products, information and suggestions are intended for use by persons having technical skill and know-how in the industry. Such persons are responsible, at their sole discretion and risk, to satisfy themselves regarding the suitability of Pelseal’s products, information and suggestions for their particular use and circumstances. Any handling precaution information is given with the understanding that those using it will satisfy themselves that their particular use conditions present no health or safety hazards. **Warranty** For a period of one (1) year from the certification date listed on Pelseal’s products, Pelseal certifies that the products meet Pelseal’s specifications in effect as of such certification date. Pelseal shall not be responsible for any failure arising out of, and this limited warranty shall be rendered null and void by, any one or more of the following: (i) Pelseal is not paid in full for the products purchased by buyer, (ii) buyer or any end-user does not cooperate with Pelseal’s reasonable investigation of any alleged non-conforming product, or (iii) damage in transit, abuse, misuse, improper maintenance, acts of nature, accidents (e.g. dropping the products), alteration of the product or causes beyond Pelseal’s reasonable control. In the event that any Pelseal product is not as expressly warranted above, Pelseal will, at its sole option, either allow credit or replace such non-conforming product if such product is returned by buyer to Pelseal, freight prepaid. **OTHER THAN THE WARRANTY SET FORTH ABOVE, PELSEAL MAKES NO OTHER WARRANTIES OR REPRESENTATIONS OF ANY KIND, EXPRESS OR IMPLIED, AS TO THE CONDITION, DESCRIPTION, FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR AS TO ANY OTHER MATTER. PELSEAL SHALL NOT BE LIABLE OR RESPONSIBLE FOR ANY CONSEQUENTIAL, INDIRECT, INCIDENTAL, PUNITIVE OR SPECIAL DAMAGES.**

3161 State Road, Unit G, Bensalem, PA19020 USA
Questions? Visit us at: www.pelseal.com Or call (215)-245-0581
fx (215)-245-7606 email: sales@pelseal.com

Rev:1/1/2023